

GARE 14

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Gare SY-Hi-Lo SY-4418

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name

Gare Inc.

Address (Number, Street, City, State and ZIP Code)

165 Rosemont Street

Haverhill, MA 01831

Emergency Telephone Number

Regional Poison Control Center (Poisondex System)

Telephone Number for Information **978-373-9131**

Date Prepared **November 2004**

Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

NON-TOXIC

CONFORMS TO
ASTM D 4236

This material has been evaluated under the provision of LHAMA (Labeling of Hazardous Art Materials Act) and California Proposition 65 by a board certified toxicologist. This product was judged to be non-toxic and non-flammable under the proposed use conditions. No special warning label is required under the provision of LHAMA or California Proposition 65. The label should state, "Conforms to ASTM D 4236"

Section III—Physical/Chemical Characteristics

Boiling Point Water	212° F	Specific Gravity (H ₂ O = 1)	1.-1.2
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	As water

Solubility in Water **Emulsion, in solution.**

Appearance and Odor **Milky white, slight ammonia odor.**

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) Will not burn	Flammable Limits N/A	LEL N/A	UEL N/A
--	-----------------------------	----------------	----------------

Extinguishing Media **Not combustible. This is a water-based product.**

Special Fire Fighting Procedures **Wear self-contained breathing apparatus approved by MSHA/NIOSH.**

Unusual Fire and Explosion Hazards **Material can splatter above 212°F. Polymer film can burn.**

Section V—Reactivity Data

Stability	Unstable		Conditions to Avoid	N/A
	Stable	x		
Incompatibility (<i>Materials to Avoid</i>) None known				
Hazardous Decomposition or Byproducts N/A				
Hazardous Polymerization	May Occur		Conditions to Avoid	N/A
	Will Not Occur	x		

Section VI—Health Hazard Data

Route(s) of Entry	Inhalation?	Non-toxic	Skin?	Ingestion?
Health Hazards (<i>Acute and Chronic</i>) Non-toxic				
Carcinogenicity	Not suspected	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure N/A				

Medical Conditions

Generally Aggravated by Exposure **May be irritating to eyes and skin. Vapor spray mist can cause headache, nausea and irritation of the nose, throat and lungs.**

Emergency and First Aid Procedures

Eye contact: Flush with water for 15 minutes.

Ingestion: Call Physician. Skin contact: Wash with soap and water.

Section VII—Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled	Clean up with dry and damp paper towels. Spills will be slippery.
Waste Disposal Method	Follow Federal, State and local regulations for disposal.
Precautions to Be Taken in Handling and Storing	Keep bottle covers properly tightened.
Other Precautions	Keep from freezing.

Section VII—Control Measures

Respiratory Protection (<i>Specify Type</i>)	Not for spray application.			
Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (<i>General</i>)	N/A	Other	N/A
Protective Gloves	Only if irritation occurs		Eye Protection	Avoid eye contact
Other Protective Clothing or Equipment	Wear apron or smock			
Work/Hygienic Practices	Maintain personal and work area cleanliness			