

GARE 50

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Gare Magic Dust

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's name

Gare Inc.

Address (Number, Street, City, State and ZIP Code)

165 Rosemont Street

Haverhill, MA 01831

Emergency Telephone Number

Regional Poison Control Center (Poisondex System)

Telephone Number for Information **978-373-9131**

Date Prepared **November 2004**

Signature of Preparer (optional)

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

Crushed Ceramic Glass

CAUTION
READ WARNING

CONFORMS TO
ASTM D 4236

This material has been evaluated under the provision of LHAMA (Labeling of Hazardous Art Materials Act) and California Proposition 65 by a board certified toxicologist. This product was judged to be (*acutely, chronically*) *toxic or flammable* under the proposed use conditions.

A special warning label is required under the provision of LHAMA and/or California Proposition 65 (label information).

The label should state, "Conforms to ASTM D 4236"

Section III—Physical/Chemical Characteristics

Boiling Point	Water	N/A	Specific Gravity (H ₂ O = 1)	2.5
Vapor Pressure (mm Hg)		N/A	Melting Point	over 1000°F
Vapor Density (AIR = 1)		N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Essentially insoluble			
Appearance and Odor	Granular, clear glass			

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used)	Will not burn.	Flammable Limits	N/A	LEL	N/A	UEL	N/A
Extinguishing Media	Not combustible, glass.						
Special Fire Fighting Procedures	None						
Unusual Fire and Explosion Hazards	None						

(Reproduce locally)

OSHA 174 Sept. 1985

Section V—Reactivity Data

Stability	Unstable		Conditions to Avoid N/A
	Stable	x	
Incompatibility (<i>Materials to Avoid</i>) None known			
Hazardous Decomposition or Byproducts N/A			
Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	x	

Section VI—Health Hazard Data

Route(s) of Entry	Inhalation? Yes	Skin? No	Ingestion? Yes
Health Hazards (<i>Acute and Chronic</i>) Can scratch or irritate eyes. May cause skin irritation or dryness.			

Carcinogenicity	NTP?	IARC Monographs?	OSHA Regulated?
-----------------	------	------------------	-----------------

Not suspect.

Signs and Symptoms of Exposure	Irritation at contact point.
Medical Conditions	Generally Aggravated by Exposure None known

Emergency and First Aid Procedures	Eye contact: Flush with water for 15 minutes.
------------------------------------	--

Skin contact: Wash with soap and water.

Section VII—Precautions for Safe Handling and Use	
Steps to Be Taken in Case Material Is Released or Spilled	Clean up with damp paper towels.

Waste Disposal Method	Follow Federal, State and Local regulations for disposal.
-----------------------	--

Precautions to Be Taken in Handling and Storing	Keep out of reach of children. Keep bottle covers properly tightened.
---	--

Other Precautions	When using do not eat, drink, or smoke. Wash hands immediately after use. Avoid making dust.
-------------------	---

Section VII—Control Measures

Respiratory Protection (<i>Specify Type</i>) Not for spray application.			
Ventilation	Local Exhaust	When firing kilns.	Special N/A
	Mechanical (<i>General</i>)	N/A	Other N/A
Protective Gloves		Eye Protection Avoid eye contact.	
If irritation occurs or over cuts and wounds			
Other Protective Clothing or Equipment		Wear apron or smock.	
Work/Hygienic Practices Maintain personal and work area cleanliness.			