

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION OF SUBSTANCE AND COMPANY PREPARING INFORMATION

Identity: Specialty Glazes

Code: NTG 9018, 9060, 9203, 9216, 9407, 9554, and 9555

Uses: Glaze for ceramic use

Manufacturer's Name: Gare Inc.,

Address: 165 Rosemont St., Haverhill, MA 01832

Tel Phone: 978-373-9131

Emergency Tel: Regional Poison Control Center

SECTION 2 - HAZARD IDENTIFICATION

Mixture is considered non-hazardous. Contains small amounts of potential carcinogens: Crystalline silica (quartz) may be present (1-2% in product). Other ingredient present at 99% have unknown acute toxicity

SECTION 3 – COMPOSTION/INFORMATION ON INGREDIENTS

Specialty Glazes are non-hazardous water based mixtures of ceramic material containing non-lead frits, clay, and other minerals and color pigments.

SECTION 4 – FIRST-AID MEASURES

Inhalation: May cause irritation, remove from exposure.

Skin: May cause irritation, Wash skin with soap and water.

Eye: May cause irritation, Flush eyes with large quantities of water for at least 15 minutes. If irritation is present after washing, contact a physician.

Ingestion: Contact a physician

SECTION 5 – FIRE-FIGHTING MEASURES

Special Fire-Fighting Procedure – None
Extinguishing Media – None

Unusual Fire or Explosion Hazards - None
Hazardous Combustion Products - None

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Inhalation: May cause irritation, remove from exposure.

Skin: May cause irritation, Wash skin with soap and water.

Eye: May cause irritation, Flush eyes with large quantities of water for at least 15 minutes. If irritation is present after washing, contact a physician.

Ingestion: Contact a physician

SECTION 7 – HANDLING AND STORAGE

When used according to the label directions and fired in a ceramic kiln they produce a smooth glaze (glass-like) finish on formed and bisqued ceramic articles.

Precautions for safe handling: None
Work Practices - None
Procedures for Leaks or Spills - None

Procedure/Equipment - None
Conditions for safe storage: None

SECTION 8 – EXPOSURE CONTROL/PERSONAL PROTECTION

Exposure Limits - These non-hazardous liquids are water based mixtures of ceramic material containing non-leaded frits, clay, silica and other minerals and color pigments. These mixtures have no TLV or PEL

Engineer Control – Adequate ventilation (local exhaust) if sprayed

Personal Protective Equipment - For spray application –eye protection and respirators and protective clothing such as aprons

SECTION 13 – DISPOSAL INFORMATION

Follow Local, State And Federal Regulations

SECTION 14 – TRANSPORTATION INFORMATION

UN Number - None
UN Proper Shipping Name - None
Transportation Hazard Class - NA
Packing Group - None
Environmental Hazard - None
Special Precautions - None

SECTION 15 --REGULATORY INFORMATION

Silica, (quartz) is listed by California Proposition 65
Silica (quartz), is listed on the IARC, OSHA, or NTP carcinogen list.
SARA Section 313 – None
See local requirements.
Conforms to ASTM D 4236 This material has been evaluated under the provision of LHAMA (Labeling of hazardous art material act). This product is judged to be non-toxic and non-flammable under proposed use conditions. No special warning is required under the provisions of LHAMA or California Proposition 65

SECTION 16 - OTHER INFORMATION

Date Prepared: August 7, 2012, **Replaces MSDS dated NA**